



# ULTRON Range

**Dirt-resistant and stain-resistant sealing treatment for industrial application on polished porcelain ceramic tiles, specific for SUPERSHINE/LUXURY machines**

**ULTRON** is a water-based inerting sealing treatment specifically developed for industrial application on polished porcelain ceramic tiles by using SUPERSHINE / LUXURY systems. The application of the product provides a significant sheen increase of the material, removes the aesthetics defects, even the deep ones, caused by the mechanical polishing. The product provides also excellent dirt-resistance, stain-resistance and etching resistance to the surface, providing a deep and vitreous effect. The product catalyzes tenaciously inside the superficial pores and roughness of the material that opened up during the mechanical finishing, sealing the surface and increasing the abrasion-resistance against foot-traffic.

**ULTRON** protects the surface from grout, stains, foot traffic, and chemical aggressions. **ULTRON** provides extremely long-lasting protection that resists UV rays, bad weather conditions, and also the use of acid-based and alkaline-based cleaners thanks to its formula enriched with synthetic compounds. Its formula doesn't yellow over time. The unique formulation makes the product easy to apply on the line of production. The product is not dangerous for human health nor for the environment.

## APPLICATION FIELD

The product is suitable for application on mechanically polished porcelain ceramic tiles: full-body polished tiles, glazed polished tiles, brushed tiles

## CONSUMPTION

The coverage of the product depends on the initial condition of the surface after the mechanical polishing. Generally, the product covers, from **25 – 40 m<sup>2</sup>/Kg** with an average of **30 - 35 m<sup>2</sup>/Kg**

## APPLICATION TOOLS

Application on industrial production line, specific for SUPERSHINE / LUXURY machines.



## Industrial production line treatments

**ULTRON Range** - Dirt-resistant and stain-resistant sealing treatment for industrial application on polished porcelain ceramic tiles, specific for SUPERSHINE/LUXURY machines



### APPLICATION

Product application is done with LUXURY / SUPERSHINE systems, always after mechanical polishing, on reasonably dry and clean material. The products from the ULTRON range does not require the preliminary treatment with acid cleaning products, except for surfaces with an high sensibility to chemical etching. Apply the product by using the specific application system and brush the surface by using the specific tools, paying attention to dispense the most suitable amount of product to achieve the desired filling and aesthetic result, according to the initial condition of the surface after the polishing. The surface must be completely clean and free from treatment residues at the end of the brushing procedure. For this type of application we suggest running preliminary tests since, in the industrial application, different factors may affect the product applicability and the achievable result. Depending on the specifics of the ceramic surface and the available application and brushing system, the product may need more than a single application to achieve the desired result.

### APPLICATION TOOLS CLEANING

After the application the used tools can be cleaned by using water.

### SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

### STORAGE

Keep the container tightly closed and store in a cool, dry place.

### SHELF TIME

24 months in the original, sealed packaging, stored in a cool, dry place.

### PACKAGING

25 liter tanks; 600 liter; 1000 liter tanks



**Industrial production line treatments**

**ULTRON XX** - Dirt-resistant and stain-resistant sealing treatment for industrial application on polished porcelain ceramic tiles, specific for SUPERSHINE/LUXURY machines



**Version 0.0 – 24/05/2020**

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on [www.fabersurfacecare.com](http://www.fabersurfacecare.com) site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

*The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.*

FABERSURFACECARE.COM

