



SHOWROOM LINE



Stain Removers

SILI-GONE

Stain remover for silicone, adhesive, ink, and graffiti residues

SILI-GONE is a solvent-based gel stain cleaner for the removal of silicone, ink, and graffiti residues. Its versatile formula makes the product suitable to be applied to a wide range of materials. Its gel-like consistency makes the product ideal for vertical applications.

BENEFITS

- ✓ Great stain removal power
- ✓ Suitable for vertical applications
- ✓ Versatile

USES

Suitable for indoor and outdoor applications.

Suitable for Marble-cement agglomerates, Marble-resin agglomerates, Quartz-resin agglomerates, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Concrete Tiles, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Terracotta, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Cement grout, Limestone, Marble, Exposed brick, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff, Glass.

APPLICATION EQUIPMENT

White Pad, Direct application

APPLICATION STEPS

Before applying the product it is necessary taking a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Carefully clean the surface, making sure to remove any dust or rough dirt present.
- Protect all areas not to be treated
- Don't apply the product to overheated surfaces. The surface temperature must be between +5 and +40°C.

Application

The product is ready to use. Apply the product directly on the stain. Scrub every now and then the product on the stain using a white pad to boost the cleaning power of **SILI-GONE**.

Let the product act on the surface working the product with the white pad every now and then. Let it act for 15 to 30 minutes depending on the entity of the stain, how dated and stubborn the stain is, and the absorption level of the surface.

Once the time has passed, scrub the product on the stain again using the white pad. Proceed to remove the product from the surface using paper towels or cloths. Once **SILI-GONE** has been removed, rinse the surface with water. At the end we recommend cleaning the surface using **CLEAN 360**.

In case of stubborn residues, we recommend applying it again with the white pad this time buffing it in circular motions applying a little pressure on the pad.

MADE IN ITALY

100%



SHOWROOM LINE



APPLICATION STEPS

If the stain has improved but is not totally gone we recommend repeating the application.

When applying it on surfaces that are medium-high absorbing like terracotta and rough stones, to avoid the material to excessively absorb the product we recommend lightly wetting the surface with water. In this case, before applying **SILI-GONE** the surface must be humid.

Resume surface use

After rinsing the surface with water, wait for the floor to dry completely before opening to foot traffic.

INSTRUCTIONS AND GUIDELINES

- **SILI-GONE** needs to be used on its own. Never mix or use in conjunction with other chemicals.
- Do not apply the product on overheated surfaces
- During the application, the surface can't be exposed to direct sunlight
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

EQUIPMENT CLEANING

The equipment used can be cleaned with water and soap

PHYSICAL AND TECHNICAL DATA

Formula	Gel
Color	Clear
Odor	Light smell
Specific gravity at 20°C	1095 ± 20 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

250 ml bottles

ACCIDENTAL SPILLS

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev0.0 – 12/07/2023

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.

MADE IN ITALY

100%

FABER CHIMICA SRL

60044 FABRIANO (AN) ITALY - VIA G. CERESANI 10 - LOC. CAMPO D'OLMO
 PI-CF / VAT NUMBER 0100744021 - P: +39 0732 62 71 78
 INFO@FABERSURFACECARE.COM - FABERSURFACECARE.COM